



Connector pin no.	Cable color	Dot mark (color)	Function
A1	Light brown	■ (Black)	COM+
A2	Light brown	■ (Red)	COM-
A3	Yellow	■ (Black)	IN0
A4	Yellow	■ (Red)	IN1
A5	Light green	■ (Black)	IN2
A6	Light green	■ (Red)	IN3
A7	Gray	■ (Black)	IN4
A8	Gray	■ (Red)	IN5
A9	White	■ (Black)	SETUP
A10	White	■ (Red)	HOLD
A11	Light brown	■ (Black)	DRIVE
A12	Light brown	■ (Red)	RESET
A13	Yellow	■ (Black)	SVON
B1	Yellow	■ (Red)	OUT0
B2	Light green	■ (Black)	OUT1
B3	Light green	■ (Red)	OUT2
B4	Gray	■ (Black)	OUT3
B5	Gray	■ (Red)	OUT4
B6	White	■ (Black)	OUT5
B7	White	■ (Red)	BUSY
B8	Light brown	■ (Black)	AREA
B9	Light brown	■ (Red)	SETON
B10	Yellow	■ (Black)	INP
B11	Yellow	■ (Red)	SVRE
B12	Light green	■ (Black)	*ESTOP
B13	Light green	■ (Red)	*ALARM

The "*ALARM" and "*ESTOP" are the negative-true logic output.

Power supply for I/O signal
24 VDC
(Provided by customer)

